





LABdex



-60°C Upright Freezer LX5030UF



Email: info@labdex.com **website:** www.labdex.com



Description

-60°C Upright Freezer LX5030UF offers substantial storage space for different medical products. It is an environmentally friendly device with an adjustable temperature range of -25°C to -60°C. Designed with a microprocessor control system with LED display. The external chamber is made up of sprayed steel plate and the internal material is made up of 304 stainless steel. It has various types of alarms, such as a high or low-temperature alarm and a sensor failure alarm.

Specifications

External size (W x D x H)	470 x 490 x 1120 mm
Internal size (W x D x H)	270 x 265 x 400 mm
Capacity	30 L
Temp. range	-25°C~-60°C
Temp. accuracy	0.1°C
Control system	microprocessor control, LED digital display
Audible and visual alarm	High and low temperature alarm, sensor failure alarm
Alarm method	Sound beeps and lights flash
Refrigeration type	Direct refrigeration
Refrigerant	R404A and R23
Foam layer thickness	100 mm
Internal material	304 stainless steel
External material	Sprayed steel plate
Consumption	400 W
Power supply	AC110V/220V±10%, 50/60Hz
Package size (W x D x H)	540 x 560 x 1290 mm
Gross weight	85 kgs

Features

- ˆ Microprocessor control system with LED display
- ˆ It contains a 100mm thick foam layer
- ˆ Alarm system with buzzer sound and lamp flashing function
- ˆ It has strong cooling and low energy consumption
- ˆ Designed with a direct refrigeration system

Applications

- ˆ Used for storage of biological, pharmaceuticals, plasmas, research institutions, and other temperature-sensitive material in laboratories and blood banks.



71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.

Email: info@labdex.com | Website: www.labdex.com